



Corrigendum to “Precision 3D printing of chitosan–bioactive glass inks: Rheological optimization for enhanced shape fidelity in tissue engineering scaffolds” [Bioprinting 43 (2024) e00359]

Larissa R. Lourenço^a, Roger Borges^b, Danilo Carastan^c, Mônica B. Mathor^d, Juliana Marchi^{a,*}

^a Centro de Ciências Humanas e Naturais (CCNH), Universidade Federal do ABC (UFABC), Brazil

^b School of Biomedical Engineering, Faculdade Israelita de Ciências da Saúde Albert Einstein, Hospital Israelita Albert Einstein, Brazil

^c Centro de Engenharia, Modelagem e Ciências Sociais Aplicadas (CECS), Universidade Federal do ABC (UFABC), Brazil

^d Centro de Tecnologia das Radiações (CETER), Instituto de Pesquisas Energéticas e Nucleares (IPEN), Brazil

The authors wish to correct Equation (3) and the corresponding numerical value of Q reported in Section 2.3. The correct expression is:

$$Q = Av = (\pi r^2)v = 0.38 \text{ mm}^3 \cdot \text{s}^{-1}$$

This correction replaces the previously reported value of $Q = 0.27 \text{ mm}^3 \text{ s}^{-1}$.

Consequently, the estimated shear rate ($\dot{\gamma}$) during printing increases slightly ($\sim 13\text{--}20 \text{ s}^{-1}$ instead of $9\text{--}15 \text{ s}^{-1}$, section 3.1, first paragraph, 8th line). This adjustment does not affect the experimental data, analysis, or conclusions presented in the paper. Corrected values for Table 1 of the supplementary information are:

Table.1

Experimental rheological values after 3D printing for the studied inks.

Material	n	Shear rate [s^{-1}]
C6	0.23	20.78
CBG0.5	0.45	14.97
CBG1	0.44	15.00
CBG2	0.46	14.68
CBG5	0.58	13.47

The authors apologize for the oversight.

DOI of original article: <https://doi.org/10.1016/j.bprint.2024.e00359>.

* Corresponding author.

E-mail address: juliana.marchi@ufabc.edu.br (J. Marchi).

<https://doi.org/10.1016/j.bprint.2025.e00447>

Available online 27 October 2025

2405-8866/© 2025 Elsevier B.V. All rights are reserved, including those for text and data mining, AI training, and similar technologies.